

SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN that we, J. Barry Winder of Austin, Williamson County, Texas; Donald L. Wharry of Austin, Williamson County, Texas; John R. Schell of Austin, Travis County, Texas; Mary J. Brown of Cedar Park, Williamson County, Texas; Joy L. Murray of Austin, Travis County, Texas; Richard C. Howe of Round Rock, Williamson County, Texas; Wayne L. Soreson of Austin, Williamson County, Texas; Daniel P. Szura of Georgetown, Williamson County, Texas; and Frank Gates, Leander, Williamson County, Texas, have invented new and useful improvements in a

**A REACTIVE DISTILLATION ALKYLATION PROCESS INCLUDING
IN SITU CATALYST REGENERATION**

of which the following is a specification:

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this correspondence and all referenced enclosures are being deposited by me with the United States Postal Service as Express Mail with Receipt No. EL715550065US in an envelope addressed to the Assistant Commissioner of Patents, BOX-NEW PATENT APP., Washington, DC 20231 on March 5, 2002.

By: _____


C. James Bushman

A REACTIVE DISTILLATION ALKYLATION PROCESS INCLUDING IN SITU CATALYST REGENERATION

Field of the Invention

This invention relates to catalyst regeneration. More particularly, this invention relates to the in situ regeneration of solid acid catalysts in a unified, continuous, pressurized, reactive distillation process for the alkylation of light
5 aromatic compounds, such as benzene and cumene.

Background of the Invention

The alkylation of aromatic compounds with olefins is an established commercial technology. For example, benzene alkylated with short chain (typically 2 to about 6 carbons) hydrocarbons has value as gasoline octane enhancer. Light
10 aromatic compounds alkylated with longer chain (that is, having greater than about 8 - 10 carbon atoms) linear olefins are commonly sulfonated to produce surfactants suitable for use in detergent manufacture.

The alkylation of benzene and other light aromatic compounds has typically been carried out using hydrofluoric acid or a solid acid catalyst in a fixed bed, plug
15 flow process. For example, U.S. Patent No. 2,860,173 discloses the use of a solid phosphoric acid as a catalyst for the alkylation of benzene with propylene to produce cumene. More recently, the use of Friedel Crafts catalysts, especially aluminum chloride and certain natural zeolites and synthetic commercial sieves, as alkylation catalysts, has been taught.

20 Still more recently, alkylation of benzene and light aromatics with C_6 - C_{30} olefin co-fed with the aromatic over a solid catalyst bed in a reactive distillation column has been proposed carried out in a reactive distillation column (U.S. Patent No. 5,770,782).

25 However, there continue to be problems associated with commercial alkylation processes. For one thing, most of the above processes have practical

limits on the amount of aromatic that can be economically co-fed with the olefins, thus resulting in low yields of the desired alkylated products. The typical range for benzene to olefin mole ratio using HF alkylation technology is 4/1 to 8/1. The fixed bed, plug flow solid acid technology referred to above is practiced using a benzene/olefin molar ratio of 15/1 to 30/1. The examples proposed for reactive distillation in U.S. Patent No. 5,770,782 used a 5/1 to 20/1 benzene/olefin mole ratio for the co-fed mixture and indicate a need for mechanical mixing of the aromatic and olefin before they enter the catalyst bed to assure adequate conversion and alkylate yield.

In addition, all these processes have a significant tendency to produce polysubstituted, in particular, dialkylated aromatics. Solid acid alkylation catalysts tend to deactivate more rapidly in the presence of dialkylated aromatic products. Carbonaceous deposits and heavy organics build up on the catalyst surface, with resultant decrease in catalyst effectiveness and a need to shut the process down to regenerate the catalyst. Most of these problems are directly related to the exothermic nature of the reaction, which has a tendency to be severe and difficult to control. Regeneration is typically provided using benzene maintained in the liquid phase at a pressure of 500 plus psig and temperatures in excess of 250° C.

It is clear that a need exists for a method of alkylation of light aromatics with straight chain olefins that has high olefin conversion rates, a high selectivity for mono-substituted products, and prolonged catalyst effectiveness. Reducing the severity of operating conditions would improve the likelihood of achieving such results.

Summary of the Invention

This invention provides a unified reactive distillation process and system useful in the preparation of mono-alkylated aromatic compounds by the solid acid-catalyzed reaction of light aromatic compounds with low molecular weight, straight chain olefins, which allows for the periodic in situ regeneration of the catalyst, i.e., in the distillation column.

The aromatic alkylation process of the invention involves a reactive distillation process and comprises a continuous, pressurized process using a distillation column configuration and system including a reactive zone, a first rectification zone at the top of the distillation column for rectification and recovery of unreacted aromatic hydrocarbon feedstock, an intermediate reactive zone containing a solid acid alkylation catalyst, and a second rectification zone positioned below and in communication with the reactive zone, where unreacted aromatic hydrocarbon and olefin feedstock may be separated from the alkylation product and any by-products. Below the second rectification zone is a reboiler and means for withdrawing the alkylation product from the column. Suitably positioned injectors allow for the controlled introduction of aromatic hydrocarbon compound and olefin feedstock.

In the reactive distillation alkylation process at least a portion of a suitable olefin feedstock is introduced at a point between the intermediate catalyst zone and the upper rectification zone, and at least a portion of a suitable aromatic hydrocarbon feedstock is introduced at a point between the catalyst zone and a second, lower, rectification zone, and the aromatic hydrocarbon is refluxed upwardly through the catalyst zone to contact and react with the descending olefin feedstock in a counter-current, liquid phase reaction. In such preferred system, the conditions of the reaction require that the internal pressure in the reactive zone is maintained constant and above about 1 atmosphere, preferably between about 20 and about 200 psig, and the combination of olefin and aromatic hydrocarbon in the reboiler maintained at or near reflux such that the temperature in the reboiler stays below the thermal degradation temperature for the alkylated product, which is about

265°C, and the molar ratio of the aromatic hydrocarbon to the olefin in the liquid phase can be maintained between about 30/1 to about 100/1, preferably between about 40/1 to about 80/1.

Regeneration of the catalyst in reactive distillation alkylation process is required as a result of a build-up on the surface of the catalyst of reaction by-products that "poison" the catalyst, lessening its effectiveness and causing a loss of conversion. According to a preferred aspect of the present invention, periodic regeneration of the alkylation catalyst can be accomplished in the distillation column periodically by ceasing flow of the olefin feedstock and injecting an effective amount of a suitable paraffin into the column counter-current to the flow of the aromatic hydrocarbon feedstock and adjusting the internal column pressure and temperature in the catalyst zone to achieve the desired regeneration temperature which, as is well known in this art, is within the range of above about 175°C, generally from about 175°C. to about 250°C.

Typically, the preferred regeneration method of the invention will be to periodically inject the paraffin into the distillation column at a point below the first rectification zone and above the catalyst, whereby the paraffin intermixes with the refluxing aromatic hydrocarbon feedstock in counter-current flow through the catalyst zone and, in combination with the aromatic hydrocarbon, dilutes and dissolves the by-products and other material from the catalyst surface and transports it into the reboiler for recovery and disposal.

The use of a counter-current flow of paraffin and aromatic hydrocarbon in the column provides an unexpected reduction in the required operating pressure to achieve the desired regeneration temperature in the catalyst zone. The process permits regeneration at milder conditions, e.g., 175-250°C, than typically environmental in a fixed bed process. The temperature may be adjusted using both the internal pressure of the column and the reflux rate of the aromatic hydrocarbon. For example, at a column pressure of 125 to 370 psig, a composition of 40-90 mole % aromatic hydrocarbon with paraffin can be employed.

Brief Description of the Drawings

Fig. 1 provides a schematic representation of a continuous reactive distillation alkylation system using the catalyst regeneration process of the present invention. The depiction shows two separate and connected columns performing as a single system.

Fig. 2 is a graph showing the regeneration temperature profile throughout the column.

Fig. 3 is a graph comparing experimental data on paraffin plus benzene regeneration with simulated paraffin plus benzene regeneration.

Fig. 4 is a graph similar to Fig. 3 showing simulated regenerations at higher pressures.

Fig. 5 is a graph showing regeneration temperatures as a function of benzene reflux rates; and

Fig. 6 is a graph showing the relationship between benzene reflux at various rates as a function of the mole % benzene.

Detailed Description of Preferred Embodiments

By light aromatics or aromatic, we mean organic aromatic compounds having one or more rings and from 6-to about 20 carbon atoms, that boil at or below about 250°C under pressure conditions typical in a commercial reactor-type distillation column. The preferred members of this group are benzene, toluene, xylene, styrene, phenol and cumene, with benzene being especially preferred.

The preferred olefins include those straight chain mono-unsaturated olefins having from 2 to about 30 carbon atoms, preferably from about 8 to about 20 carbon atoms and, more preferably, from 10 to 14 carbon atoms. A particularly preferred olefin feedstock for detergent range alkylate comprises a mixture of C₆-C₁₈ olefins with C₆-C₁₈ paraffins derived from a commercial paraffin dehydrogenation process.

The preferred paraffins or paraffin feedstock suitable for use in the alkylation catalyst regeneration process of the present invention include paraffins having from C₄ to C₁₆ carbon atoms. In the case of gasoline range alkylation, paraffins of C₄ to C₁₆ carbon content, are preferred while in the case of detergent range alkylation, paraffins of C₈ to C₁₆ carbon content are preferred.

The catalyst regeneration process of the present invention is conveniently carried out in a unified, continuous reactive alkylation process such as that disclosed in co-pending application Serial No. _____, filed concurrently herewith and entitled "A Reactive Distillation Process for the Alkylation of Aromatic Hydrocarbons", the disclosure of which is hereby incorporated by reference. In that process, using a reactive distillation configuration such as that disclosed in accompanying Fig. 1, an olefin/paraffin mixture is injected below the benzene rectification zone at the top of the distillation column, but above the catalyst zone. The aromatic hydrocarbon is continuously injected at a point below the solid catalyst reactive zone and above a rectification zone, in which it can be separated from the alkylated product, paraffin and unreacted olefin that descends from the reactive zone on its way to the reboiler.

The alkylation reaction takes place primarily in the liquid phase on the solid catalyst in the reactive zone. Catalysts that may be employed for this invention include such acid zeolitic materials as W-Zeolite, beta-zeolite, acidic mordenite, acid clays, such as montmorillonite and medium pore zeolites such as ZSM-5, ZSM-12, 5 ZSM-18, ZSM-20, MCM-22, and BETA, L, Y, mordenite, as well as rare earth exchanged forms or de-aluminated forms of the listed zeolites. Other catalysts that may be employed in the practice of this invention are the fluorided versions of the above-mentioned zeolites and aluminum chloride impregnated on alumina, clays and silica-alumina. The catalyst can be maintained in place by supporting it on 10 structured packing, such as Koch-Glitch KATAMAX brand catalytic structured packing, or alternatively arranged in other ways familiar to those skilled in this art, for example, in a series of beds on perforated trays or in beds positioned in the liquid down comers of a trayed distillation column. The structured can also be used in the rectification zones, without catalyst, to improve the evaporation and 15 condensation efficiency in those zones.

During the alkylation process, as disclosed in the referenced application, the molar ratio of the aromatic hydrocarbon to the liquid phase olefin in the reactive zone is maintained through adjustment of the column internal back pressure, the aromatic hydrocarbon reflux rate, the energy input into the reboiler, the amount of 20 aromatic hydrocarbon removed while maintaining the column at or approaching total reflux, and the input flow of aromatic hydrocarbon. Coupling the reflux rate of the aromatic hydrocarbon with the relatively low introduction of additional aromatic hydrocarbon into the column will tend to increase the composition of aromatic hydrocarbon refluxing into the reactive zone and keep the molar ratio of the 25 aromatic hydrocarbon to the olefin in the reactive catalyst zone at a higher level..

The higher mole ratios of aromatic hydrocarbon to olefin that can be generated with counter-current flow of the liquid phase olefin and the higher reflux of aromatic compound into the reactive zone has been demonstrated to have several unexpected advantages:

First, the higher aromatic compound to olefin mole ratios in the reactive zone enables a larger catalyst zone, tending to stabilize the reaction and make it very isothermal in the distillation column. Prior attempts to keep an isothermal process typically involved mixing the aromatic hydrocarbon with the feed of the
5 olefin/paraffin mixture;

Second, higher energy input to the reboiler to produce the higher reflux rates will be without the risk of exceeding the thermal degradation temperature that can occur in the reboiler at temperatures exceeding 265°C. High aromatic hydrocarbon reflux rates at constant energy input will tend to decrease the reboiler temperature
10 as they force more aromatic hydrocarbon into the reboiler. Raising the internal pressure within the column can achieve higher catalyst reaction temperatures, thereby increasing yield, without the risk of exceeding a thermal degradation temperature in the reboiler.

Third, the higher aromatic hydrocarbon to olefin molar ratios, as well as the
15 isothermal nature of the reaction zone, can help increase the usable life of the catalyst. This is the result of the higher selectivity of the process of this invention for the mono-substituted alkylation, as opposed to poly-alkylation, which is known to poison most solid acid alkylation catalysts, requiring more frequent regeneration.

In the example set forth below, the regeneration process of this invention was
20 carried out in a continuous reactive distillation column depicted in Fig. 1. As shown in Fig. 1, for convenience, two separate columns were employed and designed to perform as a single reactive distillation column. Differential pressure control established vapor transport between the lower half (column 1) and the upper half (column 2). Liquid transport between upper segments (column 2) and lower
25 segments (column 1) was handled by a pump and flow control from the base of column 2.

The catalysts employed were solid acid mordenite and Y zeolites. The catalyst is granulated to a 16 x 40 U.S. mesh size, dried at an appropriate temperature to activate it, and loaded into 54 KATAMAX catalyst packing elements.

Each element has a 2 inch outside diameter and is 5.5 inches long. The mass of catalyst loaded into the column will depend on its density. However, since each of the KATAMAX elements all had the same internal catalyst volume (50.8cc), the catalyst was equally distributed by using 9 KATAMAX elements in each of Sections B, C, D, E, F, and G as shown in Fig. 1. Transition from detergent range alkylation to catalyst regeneration is made by stopping the injection of the $C_{10} - C_{14}$ paraffin/olefin mixture and replacing it with a $C_8 - C_{16}$ paraffin, while maintaining the benzene flow rate and reflux rate at the base of the column. In situ counter-current regeneration is achieved by raising the column pressure to between about 125 to 250 psig while maintaining the benzene flow at a relatively low rate with high reflux. Once the column pressure and benzene reflux become stable again, the paraffin is injected from the storage tank 1. The paraffin feed is pumped from a storage tank 1 at a controlled, rate using pump 2, Control Valve 3 and mass flow sensor 4.

The paraffin feed passes through a 4A molecular sieve bed 5 where it is dried, and then through preheater 6, where the temperature is adjusted to match the measured reflux temperature inside the column at the point of injection. The temperature is monitored and adjusted upward to match the reflux temperature as the paraffin composition in the column increases. The point of paraffin injection is conveniently the same point as the olefin feed, that is, just above the KATAMAX catalyst elements in Section B, which is just below Section A, the rectification zone that separates and refluxes the aromatic hydrocarbon (which, in each of the examples, is benzene). Benzene injection temperatures at the base of the column and at the benzene reflux injection point are adjusted upward to match the increase in the reflux temperature as the paraffin content increases. The regeneration in this counter-current manner is maintained for about 8 to about 36 hours, depending on such parameters as the type of catalyst being used and the degree to which it became deactivated.

Following regeneration, transition back to the alkylation mode is achieved by stopping the flow of paraffin while maintaining or adjusting the flow of the aromatic

hydrocarbon at the base of the catalyst bed to maintain the aromatic hydrocarbon in reflux. The column temperature is allowed to cool back to alkylation reaction temperature, while in aromatic hydrocarbon reflux condition. This is accomplished generally by gradually decreasing the column pressure back to the pressure at which the alkylation reaction takes place. The refluxing of the aromatic hydrocarbon acts to cool the column relatively quickly.

At the appropriate temperature, olefin feedstock can be re-introduced to once again begin the alkylation process. In the example below, as in the referenced application, the preferred olefin feed set forth is a paraffin/olefin feedstock derived from a paraffin dehydrogenation process. The olefin/paraffin mixture is pumped from Feed Storage Tank 1 at a controlled rate, is passed through a 4A molecular sieve bed 5 where it is dried, and then through preheater 6, where the temperature is adjusted to match the measured reflux temperature inside the column at the point of injection. The injection temperature is monitored and adjusted upward to match the measured reflux temperature inside the distillation column at the point of injection. The point of olefin feed injection is just above the KATAMAX catalyst elements in Section B, which is just below Section A, the rectification zone that separates and refluxes the aromatic hydrocarbon (which, in each of the examples, is benzene).

The aromatic hydrocarbon is pumped from storage tank 11 using pump 12, with flow controlled by control valve 13 and monitored using mass flow meter 14. Prior to injection, the aromatic hydrocarbon is also passed through a molecular sieve dryer and is heated to about 5-10°C. below its boiling point at the experimental internal column pressure. Thus, it is injected as a liquid, but generally will quickly flash due to the heat from the liquid and vapor rising out of the reboiler. As depicted in Fig. 1, the injection point 17 of the aromatic hydrocarbon is at the base of Section G, but above the rectification zone (Section H) which is immediately above the reboiler 40. This is the primary injection point and sets up the

counter-current flow of aromatic hydrocarbon with the olefin descending as a liquid from its injection point 7 (above the catalyst in Section B).

The aromatic hydrocarbon employed in the example was benzene. Benzene vapor in the column is taken overhead and condensed in cooler 19 and accumulated in vessel 20. The accumulated benzene is reinjected as reflux at point 21 in rectification zone A. As will be appreciated by those skilled in the art, this can be through level control from the accumulator vessel 20 or on flow control to the column along with a stream that removes excess benzene storage to tank 25 using the appropriate monitoring and flow controlling apparatus.

The desired operating pressure is adjusted and maintained using cascade control with appropriate nitrogen injection and venting into and out of the accumulator tank 20. The two column configuration depicted in the drawing was also used in the example. The two columns were operated as one by means of heaters and flow control valves. The benzene vapor, as it leaves Section E and flows between the columns, is maintained at the appropriate temperature and pressure by means of an electrically heated and controlled vapor transport line 26. Benzene vapor enters the base of Section D of the column at point 27 and continues through segments D, C and B. The flow between the columns is controlled at control valve 23 using a relatively low differential pressure, usually about 2 psig.

Unreacted olefin and paraffin, as well as crude alkylate product, any by-product and liquid phase benzene are accumulated in vessel 30, below Section D, cooled at 35, and pumped to the top of Section E on level control. The liquid from pump 32 is reheated at 34 to precisely the reflux temperature of the column at the injection point 35. The liquid then continues to descend through the catalyst zone (Sections E, F and G into rectification zone H and reboiler 40. Crude linear alkyl benzene product, paraffin, higher molecular weight bottoms product and trace levels of unreacted olefin, if present, removed through reboiler 40 on level control and pumped to storage in tank 45.

There are two liquid phase sample points at which the data on the crude alkylate product, as set forth in tables 1 and 2 below, were collected. Sample point A is the final product after passing through all catalyst sections. Sample point B is an intermediate product representing 50% of the catalyst residence time. A third
5 sample point, not shown, can be at the base of the benzene overhead accumulator
20. This can be used to measure benzene purity.

EXAMPLE 1

A unique feature of the reactive distillation unit of the present invention is the ability to regenerate the catalyst in situ at a set of regeneration conditions that are
10 in general milder than those required to regenerate a plug flow fixed bed catalytic reactor. Typically the fixed bed process calls for the use of pure benzene to be maintained in the liquid phase at 500 psig and 250°C regeneration temperature.

An example of catalyst deactivation and subsequent regeneration for the reactive distillation process was conducted as follows. A 1379.27 g of TOSOH
15 330Y was loaded into the 54 KATAMAX structured packing elements and placed in the reactive distillation column shown in Fig. 1. The reboiler was charged with benzene and the column was brought to reflux benzene at 50 - 52 psig column pressure. Paraffin/olefin feed shown in Fig. 1 as feed to section B was initiated at 50 g/min. Benzene injection at the base of the column, section G, was maintained
20 at 10 g/min. The reactive distillation column was operated at the conditions listed in Table 2. Samples of liquid product were removed from two sample points. Sample point A is cooled liquid product removed from the reboiler and represents the total conversion in the reactive distillation column. Sample point B is a cooled liquid sample removed from the intermediate accumulator at the base of column,
25 section D. This sample point represents the conversion at 50% of the catalyst volume. The TOSOH 330 Y zeolite solid acid catalyst was operated per the condition shown in Table 2 for a total of 118.5 hours on stream. During this operating period the TOSOH 330 Y experienced significant deactivation. The

conversion at point B was initially 99.96 % with a residual bromine index in the crude benzene, paraffin/olefin and alkylate product of 1.1 cg/g. The catalyst in sections B, C, and D experienced significant deactivation as the conversion dropped to 24.7% (Bromine Index 2185) at 118.5 hours on stream. Similarly Sections E, F, and G experienced deactivation from 100% conversion (Bromine Index non detectable) to 88.8% conversion with a residual bromine index of 829 cg/g. The catalyst deactivates from top to bottom in the distillation column. After 118.5 hours on stream, the paraffin/olefin mixture was discontinued and the column refluxed benzene at 134°C for 2 hours as the crude alkylate is washed from the catalyst bed into the reboiler. During this period the paraffin/olefin feed in the storage tank was replaced with a paraffin feed of the same molecular weight and carbon number distribution as shown in Table 1. The column back pressure is increased to 125 psig and the benzene reflux stabilizes at 125 psig. A uniform column temperature of only 172°-175°C is achieved with benzene reflux at 125 psig back pressure. Paraffin injection is initiated at 50 g/min through H101 at a point just above the first section containing the catalyst structured packing. The counter-current paraffin injection alters the composition in the column which increases the reflux temperature. The counter-current paraffin flow establishes a regeneration temperature profile as shown in Fig. 2. This increases the column temperature profile from the uniform 172-175°C with benzene reflux to the range of 187° to 205°C. Additional heating was applied to the column through skin heaters in order to reach the 200°C regeneration temperature at 125 psig. The additional heating is required to achieve the regeneration temperature due to the mechanical upper pressure limit on the reactive distillation column. The regeneration conditions used in this example are paraffin rate: 50 g/min, benzene rate 10 g/min, column back pressure 125 psig, and benzene set on total reflux at the top of the column. This counter-current paraffin regeneration was maintained for 24 hours. The number of hours can vary from 8 to 36 hours depending on the degree of deactivation of the catalyst. Following regeneration, the paraffin flow is stopped, the column is cooled

and pressure readjusted to 50 psig reaction pressure in a benzene reflux. Once the column is stable at 50 psig and under benzene reflux, the paraffin/olefin feed is re-established at the top of section G. The analysis of liquid samples from sample points A and B confirms that the catalyst has been completely regenerated.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
22

Tabl 1

Capillary GC Analysis of Paraffin/Olefin Feed		
Feed	A	B
	Weight %	Weight %
< C ₁₀	0	0
C ₁₀	1.53	1.98
C ₁₁	3.85	3.71
C ₁₂	3.83	3.83
C ₁₃	2.45	2.44
C ₁₄	0.33	0.36
C ₁₅	0	0
Total Olefin	11.99	12.32
Linear		
Paraffin		
< C ₁₀	0.18	0.07
C ₁₀	14.42	19.09
C ₁₁	31.84	29.72
C ₁₂	26.43	24.88
C ₁₃	14.42	13.25
C ₁₄	0.62	0.48
C ₁₅	0.19	0.2
Total Paraffin	88.1	87.69
Avg MW (g/mole)	163.6	162.9
Bromine No.(Cg/g)	10.8	10.4

Tabl 2

	Time on Stream (hrs.)	Sample Point B Olefin % Conv	Sample Point B Bromine Index (cg/g)	Sample Point A Olefin % Conv	Sample Point A Bromine Index (cg/g)	Paraffin + Olefin Injection Rate (g/min)	Benzene Feed Injection Rate (g/min)	Column Pressure (psig)	Average Catalyst Zone Temp. (°C)	Reflux Benzene Injection Rate (g/min)	Liquid Phase Benzene/ Olefin Mole Ratio
5	5	100	0	99.96	1.1	50.5	10.1	52	144	194	57
	7	99.94	4.2	85.3	375	49.9	9.8	52	144	192	54
	25	99.9	5	83.6	410	49.9	10.1	52	140	127	91
	28	100	3	83.6	426	49.9	10.0	52	144	211	73
10	31	100	1	83.9	450	49.7	9.8	52	144	176	54
	52	100	1	28.9	2347	49.7	10.0	51	144	163	46
	54	100	1	28.3	2151	49.5	10.0	51	141	146	53
	84.5	95.6	309	18.9	2351	49.8	9.8	51	143	167	55
	88.5	95.6	293	20.6	2222	49.5	9.8	51	144	172	59
	89.5	96.5	216	12.0	2199	50.1	10.1	52	144	171	58
15	116.5	84.5	1056	20	2080	50.1	10	52	144	177	62
	118.5	88.8	829	24.7	2185	50.1	9.8	52	144	177	65
Regeneration for 24 hours at 187-205°C using Counter current Paraffin and Benzene											
	6	100	1	100	1	49.7	10	50	141	85	30
	8	100	1	100	1	49.7	9.9	50	141	68	27
20	10	100	1	98.3	27	49.6	9.8	50	141	61	25

Example 2

The injection of paraffin above the catalyst is one means of increasing the steady state regeneration temperature in the reactive distillation column. This paraffin injection provides a temperature increase as well as additional washing
5 action to transport the by-products on the catalyst and transfers them to the reboiler. This effect of increased regeneration temperature with paraffin injection can be applied at higher pressure and will continue to achieve a stepwise advantage for reaching higher regeneration temperature at a given distillation column pressure. This effect can be modeled to determine the extent of the advantage beyond the
10 pressure limit of the experimental reactive distillation column shown in Fig. 1. Table 3 and Fig. 3 compare experimental data at 125 psig, 50 g/min of C₁₀-C₁₃ paraffin injection above the catalyst bed, and 10 g/min. benzene injected below the bed at the base of section G with distillation, simulation using ASPEN Plus 10.1. The simulation conditions are identical to the experimental operating conditions with
15 n-dodecane used to simulate the injected paraffin. The catalyst bed lies between Stage 6 and 18 for the simulation. The 125 psig pressure range is within the mechanical limit of the reactive distillation column shown in Fig. 1. Fig. 3 shows a good correlation between experimental data and the simulation. The advantage of counter-current paraffin injection and benzene at reflux can be shown by further
20 simulations at higher column back pressures. These higher pressure simulations using ASPEN Plus 10.1, were all conducted at 50 g/min n-dodecane injection, 10 g/min benzene injection into Section G and at total benzene reflux. The data for the higher pressure simulations are shown in Table 4 and graphed in Fig. 4. The simulation at 180 psig shows that a regeneration temperature of 200°C will be
25 achieved. Increasing the pressure to 260 psig can achieve a regeneration temperature of 224°C. Increasing the column back pressure to 370°C will achieve a regeneration temperature of 250°C. The simulations indicate that the combination of a counter-current paraffin injection with total benzene reflux will achieve increases in regeneration temperature of 8 to 12 degrees Centigrade while

maintaining a uniform temperature in the catalyst zone placed between stages 6 and 18. The total benzene reflux also provides the maximum liquid phase benzene concentration in the catalyst zone. Commercial regeneration of fixed bed process requires 500 psig reactor pressures to maintain the benzene in the liquid phase in order to achieve a 250°C regeneration temperature.

Table 3

Reactive Distillation Column Temperature Points	Simulation Stage Number	Benzene Simulation	Paraffin + Benzene Regeneration Simulation	Experimental Benzene Reflux Profile	Exp Paraffin + Benzene Regeneration Profile
Overhead Vapor Temp	1	170.379	170.379	171.379	167.8276
	2	170.379	170.379		
	3	170.379	170.380		
	4	170.379	170.387		
DA-220-1	5	170.380	170.634	173.439	173.3027
	6	170.388	178.316		
DA-220-2	7	170.388	178.317	173.355	179.8502
	8	170.388	178.317		
DA-220-3	9	170.388	178.317	173.138	180.136
	10	170.388	178.317		
DA-220-4	11	170.388	178.317	170.337	178.9793
	12	170.388	178.317		
TI-215	13	170.388	178.317	174.791	181.7515
	14	170.388	178.317		
DA-210-1	15	170.388	178.317	174.700	187.0356
	16	170.388	178.318		
DA-210-2	17	170.388	178.318	174.719	191.2626
	18	170.388	178.318		
DA-210-3	19	170.388	178.320	176.403	195.5427
	20	170.388	178.382		
	21	170.388	179.122		
	22	170.388	187.080		
DA-210-4	23	170.393	230.409	176.306	224.8719
Reboiler Temp	24	170.561	291.900	175.140	265.1487

Table 4
ASPEN Plus 10.1 Simulation of Effect of Paraffin Injection at the Top of the Catalyst Bed (above Stage 6) as a function of Column Back Pressure

Column Distillation Stage	Benzene Reflux @ 125 psi	Paraffin + Benzene @ 125 psi	Temperature Increase In Catalyst (C)	Benzene Reflux @ 180 psi	Paraffin + Benzene @ 180 psi	Temperature Increase In Catalyst (C)	Benzene Reflux @ 260 psi	Paraffin + Benzene @ 260 psi	Temperature Increase In Catalyst (C)	Benzene Reflux @ 370 psi	Paraffin + Benzene @ 370 psi	Temperature Increase In Catalyst (C)
Top 1	170.38	170.38	0.00	191.01	191.19	0.18	214.27	214.28	0.00	238.57	238.57	0.00
2	170.38	170.38	0.00	191.01	191.19	0.18	214.27	214.28	0.00	238.57	238.57	0.00
3	170.38	170.38	0.00	191.01	191.19	0.18	214.27	214.28	0.00	238.57	238.57	0.00
4	170.38	170.38	0.01	191.01	191.20	0.19	214.27	214.30	0.02	238.57	238.61	0.04
5	170.38	170.63	0.25	191.01	191.54	0.52	214.27	214.79	0.51	238.57	239.34	0.77
6	170.38	178.32	7.93	191.01	199.90	8.89	214.27	224.34	10.07	238.57	250.32	11.76
7	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.32	11.76
8	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.32	11.76
9	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.32	11.76
10	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.33	11.76
11	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.34	11.77
12	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.42	11.85
13	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	250.85	12.28
14	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	253.09	14.52
15	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.34	10.07	238.57	263.78	25.21
16	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.35	10.07	238.57	304.99	66.42
17	170.38	178.32	7.93	191.01	199.90	8.89	214.28	224.39	10.12	238.57	364.42	125.86
18	170.38	178.32	7.93	191.01	199.91	8.89	214.28	224.70	10.43	238.57	410.14	171.57
19	170.38	178.32	7.94	191.01	199.92	8.91	214.28	226.83	12.56	238.57	446.67	208.11
20	170.38	178.38	8.00	191.01	200.05	9.04	214.28	239.46	25.19	238.57	466.16	227.59
21	170.38	179.12	8.74	191.01	204.99	13.97	214.28	288.01	73.73	238.56	477.54	238.97
22	170.38	187.08	16.70	191.01	235.15	44.14	214.28	350.28	136.01	238.56	482.38	243.82
23	170.38	230.41	60.03	191.01	299.93	108.91	214.28	373.54	159.26	238.56	484.47	245.91
Reboiler 24	170.38	291.90	121.52	191.01	335.39	144.37	214.28	383.44	169.17	238.58	485.40	246.82

The data in Table 4 show that at high benzene reflux rates which achieve greater than 80 mole % benzene composition in the column, the paraffin injection provides an unexpected 7 to 15°C temperature increase at all pressures from 125 psig to 370 psig. This confirms the experimental results of Example 2 as seen in Table 3.

Example 3

Another mode of column operation can also be used to achieve high regeneration temperatures without significant increases in column pressure. This mode of operation also uses counter-current paraffin injection at the top of the catalyst bed and injection of benzene below the catalyst but maintained at reflux. A significant unexpected advantage from reducing the benzene reflux rate with paraffin injection was observed through ASPEN Simulation. Target regeneration temperatures in the range of 200° to 250°C could be achieved by reducing the benzene reflux from 150 g/min down to 18 g/min while maintaining liquid phase benzene molar compositions of 50% to 87% in the catalyst zone. ASPEN Plus 10.1 using a RAD FRAC Model was used to determine the composition in the distillation column and the temperature in the catalyst zone. Simulation data is summarized in Table 5 and plotted in Fig. 5 and Fig. 6. The data shows that a steady state regeneration temperature of 200°C within the catalyst bed (Stage 6 to Stage 18) can be achieved while maintaining a benzene liquid phase mole fraction of 67 mole %. This column composition and temperature is achieved at a reflux rate of 54 g/min of benzene at the top of the column. Similarly, a regeneration temperature of 223°C is achieved with a further reduction of benzene reflux to 18 g/min while still maintaining a liquid phase molar benzene composition of 49 mole % in the catalyst zone. These compositions can be maintained for the 8 to 36 hours required to regenerate the catalyst.

Table 5

ASPEN Plus 10.1 RAD FRAC Simulation of Counter Current n-dodecane and Benzene Reflux at 125 psig, 50 g/min C12, 10 g/min Benzene

	Benzene Reflux Rate 150 g/min		Benzene Reflux Rate 54 g/min		Benzene Reflux Rate 18 g/min	
Simulation Stage Number	Internal Temperature (C)	Benzene Liquid Mole Fraction	Internal Temperature (C)	Benzene Liquid Mole Fraction	Internal Temperature (C)	Benzene Liquid Mole Fraction
1	176.51	1.00000	176.04	0.99998	176.04	0.99994
2	176.51	1.00000	176.05	0.99974	176.08	0.99932
3	176.52	1.00000	176.23	0.99686	176.54	0.99193
4	176.53	0.99985	178.38	0.96204	182.08	0.90344
5	176.87	0.99461	200.69	0.67613	223.78	0.49139
6	186.55	0.87617	200.69	0.67613	223.78	0.49139
7	186.55	0.87618	200.69	0.67613	223.78	0.49139
8	186.55	0.87618	200.69	0.67613	223.78	0.49140
9	186.55	0.87617	200.69	0.67613	223.78	0.49141
10	186.55	0.87617	200.69	0.67615	223.77	0.49147
11	186.55	0.87617	200.68	0.67623	223.74	0.49164
12	186.55	0.87618	200.65	0.67657	223.66	0.49220
13	186.55	0.87618	200.62	0.67685	223.59	0.49264
14	186.55	0.87618	200.62	0.67686	223.58	0.49269
15	186.55	0.87618	200.62	0.67687	223.56	0.49286
16	186.55	0.87618	200.61	0.67694	223.48	0.49338
17	186.55	0.87618	200.58	0.67724	223.22	0.49510
18	186.55	0.87617	200.43	0.67865	222.36	0.50088
19	186.55	0.87616	199.78	0.68514	219.41	0.52122
20	186.72	0.87450	199.87	0.68420	219.46	0.52084
21	188.28	0.85885	200.40	0.67896	219.76	0.51876
22	201.14	0.75098	203.30	0.65123	221.34	0.50780
23	250.36	0.49332	217.20	0.53703	229.26	0.45651
24	306.20	0.30367	258.66	0.30356	258.66	0.30356

As seen in Table 5, at operating pressures as low as 125 psig and with sufficient paraffin injection, one can achieve a significant increase in column regeneration temperature by reducing the benzene reflux rate but still maintain significant and needed benzene concentration in the column. Thus, as seen from
5 the data in Table 5, a reduction of the benzene concentration from 87 mole % to 50 mole % will shift the column regeneration temperature from about 186°C to about 250°C.

As noted above, the counter-current paraffin injection permits a selection and tailoring of the regeneration conditions to suit a given catalyst. Some catalysts may
10 require higher benzene concentrations at a given regeneration temperature. Those conditions can be achieved with paraffin injection and by adjusting the benzene reflux rate. Thus, one can achieve regeneration temperature at lower pressure and still maintain proper benzene composition.

Modifications of the apparatus, procedures and conditions disclosed herein
15 that will still embody the concept of the improvements described should readily suggest themselves to those skilled in the art, and are intended to be encompassed within the spirit of the invention presently disclosed herein as well as the scope of the appended claims.